

### **CONSTRUCTION PRODUCTS REGULATION 2011**

### **DECLARATION OF PERFORMANCE**

DoP Number: DPL-AG 5150

1. Unique Identification code of the product –type:

LAL1440, LAL1441, LAL1442, LAL1444, LAL1445, LAL1446, LAL1449, LAL1450, LAL1451, LAL1453, LAL1454, LAL1455, LAL1465, LAL1466, LAL1467, LAL1468, LAL1470, LAL1471, LAL1473, LAL1474, LAL1475, LAL1476, LAL1477, LAL1478, LAL1416, LAL1417, LAL1419, LAL1419, LAL1420, LAL1422, LAL1423, LAL1425, LAL1426

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

LAL1440, LAL1441, LAL1442, LAL1444, LAL1445, LAL1446, LAL1449, LAL1450, LAL1451, LAL1453, LAL1454, LAL1455, LAL1465, LAL1466, LAL1467, LAL1468, LAL1470, LAL1471, LAL1473, LAL1474, LAL1475, LAL1476, LAL1477, LAL1478, LAL1416, LAL1417, LAL1419, LAL1419, LAL1420, LAL1422, LAL1423, LAL1425, LAL1426

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

For use on fire and smoke compartmentation doors, when fitted in accordance with the manufacturer's fitting instructions.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5)

GARG, GARGS, TUFF, ELITE, SICHERN
D. P. Garg & Co. Pvt. Ltd.
B-210B, Phase-2, Noida
District – Gautam Budh Nagar
Pin Code- 201 305 (U.P.) – INDIA

5. Where applicable, name and contact address of the authorized representative whose mandated covers the tasks specified in Article 12(2):

N/A

# 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 1

## 7. In case of the declaration of performance concerning a construction product covered by a harmonized standard.

EN 12209: 2003 incorporating Corrigendum N° 1 Notified product certification body No. 2812 performed the determination of the product type on the basis of type testing (including sampling); initial inspection of the manufacturing plant and of the factory production control and continuous surveillance; assessment and evaluation of factory production control; and issued the certificate of constancy of performance of the product.

### 8. European Technical Assessment:

N/A

#### 9. Declared Performance

Essential characteristic Self Closing	Performance  Mechanical & Fire test evidence:  WIL 371136, 371136-1, 371136-3 &  371533	Harmonised technical specification
	WF No. 377588	
5.4.2 Closing force	Grade 4, Up to 100 kg door mass, 25N max. closing force	EN 12209:2003/ AC 2005
5.1.2 Re-latching force of latch bolt	Greater than 2.5 N	
Essential characteristic Durability of self closing	Performance	Harmonised technical specification
5.3.1 Durability of latch action	Grade M, 200,000 test cycles, 25N side load on latch bolt	
Ability to maintain the door in the closed position and not contribute to the spread of fire	Grade 1	EN 12209: 2003 /
Dangerous Substances Annex ZA3	The materials in the product(s) do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.	AC 2005

**10.** The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of the performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by:

Mr. Sandip Garg

Director

Date of issue: 20/01/2017

D. P. Garg & Co. Pvt. Ltd. B-210B, Phase-2, Noida District – Gautam Budh Nagar Pin Code- 201 305 (U.P.) – INDIA

This Declaration of Performance is issued on a standard template provided by the GAI for use in the door and hardware industries. There is no implied endorsement of the content, which is the responsibility of the issuing company.

The Guild of Architectural Ironmongers BPF House, 6 Bath Place, Rivington Street, London, EC2A 3JE

Tel: +44 (0) 20 7033 2480 Fax: +44 (0) 20 7033 2486