

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-AG5216

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product.

D.P. Garg & Co. Pvt. Ltd Range of Mortice Locks See Annex A

Intended use: For use on fire/smoke compartmentation doors.

Essential characteristics	Performance	Harmonised technical specification
Mechanical test evidence: WIL 400657, WIL 400660 & WIL 400662 Fire test evidence: WF 376740, WF 376741 & WF 377588 iss.9		
Self-closing 5.4.2 Closing force 5.1.2 Re-latching force of latch bolt	Grade 7 = 100kg door mass with 15N maximum closing force >2.5N	EN 12209:2003 / AC:2005
Durability of self-closing 5.3.1 Durability of latch action	Grade M = 200,000 cycles with 25N side load on latch bolt.	
Ability to maintain the door in the closed position and not contribute to its spread of fire 5.2.1 Resistance to side load on latch bolt	Grade 1: 2kN	
5.5 Suitability for use on fire/smoke doors	Grade 1: suitable for use on fire/smoke resistant door assemblies	
Dangerous substances	Pass: the materials in the lock do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations (1)	

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-AG5216

Placed on the market under the name of:

**D.P. Garg & Co. Pvt. Ltd.
B-210B, Phase-2
Noida-201305
Gautam Budh Nagar
(U.P.) India**

and produced in the manufacturing plant:

E000323-1

This is coded format, and the information is held by the Notified Body.

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard:

EN 12209:2003 / AC:2005

Under System 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on **16/10/2020** and re-issued on **21/12/2023** and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, or unless suspended or withdrawn by the Notified Product Certification Body.

CE Marking certificate valid to: **20/12/2026**

ERO Project Reference: **ERO 034621 P2015**



**Pascal Coget
General Manager - European Certification**

CSF408-NL 8.0

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-AG5216

Annex A

Model No	Description	Backset	Centres
LAL1610	70mm 6 Lever Lock Square Forend	48mm	57mm
LAL1611	70mm 6 Lever Lock Radiused Forend	48mm	57mm
LAL1615	70mm Euro Profile Cylinder Lock Body Square Forend	48mm	57mm
LAL1616	70mm Euro Profile Cylinder Lock Body Radiused Forend	48mm	57mm
LAL1620	70mm Flat Latch Square Forend	48mm	N/A
LAL1621	70mm Flat Latch Radiused Forend	48mm	N/A

Forends available in the following finishes:

ANT	Antique	MBZ	Matt bronze
ABR	Antique brass	MSB	Matt satin brass
ABZ	Antique bronze	MEB	Mirror electro brass
OAC	Antique copper	ONP	Nickel plated
BNP	Black nickel	ORB	Oil rub bronze
BZP	Bright zinc plated	OPB	Polished brass
OCP	Chrome plated	PCP	Polished chrome plated
DBR	Dull electro brass	PNP	Polished nickel plated
DXB	Durosil epoxy black	PSS	Polished stainless steel / mirror
DSL	Durosil silver	RGL	Rose gold
OEB	Electro brass	SBR	Satin brass
EXB	Epoxy black	SCP	Satin chrome plated
EXW	Epoxy white	SNP	Satin nickel plated
OFB	Florentine bronze	OSS	Satin stainless steel
GAL	Galvorite	SLV	Silver
GSL	Galvorite silver	SSS	Simulated satin finish
OGN	Graphite nickel	OUB	Urban bronze
MBN	Gun metal	UDB	Urban dark bronze
MAB	Matt antique brass	USC	Urban satin copper
OMB	Matt black		

Brand names:

GARG, GARGS, TUFF, ELITE, SICHERN